

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)



**DoP Nr: KR-032002**

Version 1.1 / July 2015

Page 1 of 2

- 1. Unique identification code of the product-type:**  
PENOSIL Roof & Facade Crystal Sealant (transparent)

---

- 2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):**  
Batch number: see packaging of the product

---

- 3. Intended use or uses of the construction product:**  
Sealant for façade elements, for interior application only.

---

- 4. Construction product in accordance with applicable harmonised specifications:**  
EN 15651-1:2012: Type F-INT

---

- 5. Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5):**  
OÜ KRIMELTE  
Suur-Paala 10  
13619 Tallinn  
ESTONIA

---

- 6. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**  
Not relevant (see 5)

---

- 7. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:**  
System 4 for the type testing. / System 4 for the reaction to fire

---

- 8. In case of the declaration of performance concerning a construction product covered by a harmonised standard:**  
Not relevant.

---

**9. Declared performance:**

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)



**DoP Nr: KR-032002**

Version 1.1 / July 2015

<u>Essential characteristics:</u>	<u>Performance:</u>	<u>Harmonised technical specification</u>
<b>Reaction to fire</b> (EN 13501-1:2007 + A1:2010)	Class F	EN 15651-1: 2012
<b>Release of chemicals dangerous to the environment and health</b>	NPD	
<b>Water tightness and air tightness, as:</b>		
• Resistance to flow (EN ISO 7390)	≤ 5 mm	
• Loss of volume (EN ISO 10563)	≤ 45 %	
• Tensile properties (i.e. elongation at break) at 23°C (EN ISO 8339)	≥ 25 %	
<b>Durability:</b>	Pass	
Conditioning method A / Tested on glass, without primer		

**10. Declaration:**

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.  
Signed for and on behalf of the manufacturer by:

Margus Matsal

Product Manager  
13619 Tallinn, Estonia  
02/07/2015