

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)



**DoP Nr: KR-030002**

Version 2 / March 2022

Page 1 of 2

---

**1. Unique identification code of the product-type:**

PENOSIL Kitchen & Bath Fresh Silicone Sealant

---

**2. Intended use/uses:**

Sealant for facade for interior and exterior application (intended for use in cold climates)  
EN 15651-1; type F-EXT-INT-CC, class 25HM

Sealant used for sealing glazing applications (intended for use in cold climates)  
EN 15651-2 G-CC: Class 25HM

Sealant for joints in sanitary areas  
EN 15651-3 S: Class XS1

---

**3. Manufacturer:**

Wolf Group OÜ  
Suur-Paala 10  
13619 Tallinn  
ESTONIA

---

**4. Authorized representative:**

Not relevant.

---

**5. System or systems of assessment and verification of constancy of performance (AVCP):**

System 3 for the type testing.  
System 3 for the reaction to fire.

---

**6. Harmonised standard:**

EN 15651-1:2012  
EN 15651-2:2012  
EN 15651-3:2012

**Notified body/ies:**

1292 - FUNDACION TECNALIA RESEARCH & INNOVATION.

---

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)



**DoP Nr: KR-030002**

Version 2 / March 2022

## 7. Declared performance:

<u>Essential characteristics:</u>	<u>Performance:</u>	<u>Harmonised technical specification</u>
<b>Reaction to fire</b> (EN 13501-1:2007 + A1:2010)	Class E	EN 15651-1: 2012 EN 15651-2: 2012 EN 15651-3: 2012
<b>Release of chemicals dangerous to the environment and health</b>	NPD	
<b>Water tightness and air tightness, as:</b>		
• Resistance to flow (EN ISO 7390)	≤ 3 mm	
• Loss of volume (EN ISO 10563)	≤ 10 %	
• Tensile properties (i.e. at maintained extension) at -30°C (modif. EN ISO 8340)	NF	
• Tensile properties at maintained extension after water immersion (EN ISO 10590)	NF	
• Elastic recovery (EN ISO 7389)	≥ 60 %	
• Adhesion/cohesion properties after exposure to heat, water and artificial light (EN ISO 11431)	NF	
• Microbiological growth (EN ISO 846, proc. B)	0	
<b>Durability:</b>	Pass	
Conditioning method A / Tested on glass, anodized aluminium, and mortar M2, without primer		

## 8. Declaration:

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Kuldar Kongo

Product Manager  
13619 Tallinn, Estonia  
24/03/2022