

Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

DoP Nr: KR-023001



Version 3 / May 2022

Page 1 of 2

1. Unique identification code of the product-type:

PENOSIL Premium FireStop Silicone

2. Intended use/uses:

Sealant for joints on the external and internal side of facade elements (intended for use in cold climates: -30 °C)

(F-EXT-INT-CC: class 25HM)

3. Manufacturer:

Wolf Group OÜ

Suur-Paala 10

13619 Tallinn

ESTONIA

4. Authorised representative:

Not relevant

5. System or systems of assessment and verification of constancy of performance (AVCP):

System 3 for the type testing.

System 3 for the reaction to fire.

6. Harmonised standard:

EN 15651-1:2012

Notified body/ies:

1292 - FUNDACION TECNALIA RESEARCH & INNOVATION

0074 - GINGER CEBTP

Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

DoP Nr: KR-023001



Version 3 / May 2022

7. Declared performance:

<u>Essential characteristics:</u>	<u>Performance:</u>	<u>Harmonised technical specification</u>
Reaction to fire (EN 13501-1)	B-s3, d0	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	
Water tightness and air tightness, as:		
• Resistance to flow (EN ISO 7390)	≤ 3 mm	
• Loss of volume (EN ISO 10563)	≤ 10 %	
• Tensile properties (i.e. at maintained extension) at -30 °C (modif. EN ISO 8340)	NF	
• Tensile properties at maintained extension after water immersion (EN ISO 10590)	NF	
Durability:	Pass	
Conditioning method A / Tested on anodized aluminium and mortar M2 substrates, without primer.		

NPD = No Performance Determined

NF = No Failure

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kuldar Kongo
Product Manager
13619 Tallinn, Estonia
27.05.2022