

Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)



DoP Nr: KR-714001

Version 1 / March 2021

Page 1 of 2

1. Unique identification code of the product-type:

PENOSIL Standard Neutral Silicone (transparent)

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see packaging of the product

3. Intended use or uses of the construction product:

Sealant for facade for interior and exterior application.
Sealant used for sanitary applications.

4. Construction product in accordance with applicable harmonised specifications:

EN 15651-1:2012: Type F-INT-EXT: CLASS 12,5E
EN 15651-3:2012: Type S: CLASS S1

5. Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5):

OÜ KRIMELTE
Suur-Paala 10
13619 Tallinn
ESTONIA

6. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not relevant (see 5)

7. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 3 for the type testing. / System 4 for the reaction to fire

8. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

FUNDACION TECNALIA RESEARCH & INNOVATION (notified body nr. 1292) performed type testing under system 3 and issued test reports.

Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)



DoP Nr: KR-714001

Version 1 / March 2021

9. Declared performance:

<u>Essential characteristics:</u>	<u>Performance:</u>	<u>Harmonised technical specification</u>
Reaction to fire	Class F	EN 15651-1: 2012 EN 15651-3: 2012
Release of chemicals dangerous to the environment and health	NPD	
Water tightness and air tightness, as:		
• Resistance to flow	≤ 3 mm	
• Loss of volume	≤ 25 %	
• Tensile properties at maintained extension	NF	
• Adhesion/cohesion at variable temperatures	NF	
• Adhesion/cohesion at maintained extension after water immersion	NF	
• Tensile properties after immersion in water, elongation at break	≥ 25 %	
• Microbiological growth	0+	
Durability:	Pass	
Conditioning method B / Tested on aluminium, without primer		

10. Declaration:

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Kuldar Kongo

Product Manager
13619 Tallinn, Estonia
16/03/2021