

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)



**DoP Nr: KR-043001**

Version 3 / November 2020

Page 1 of 2

- 1. Unique identification code of the product-type:**  
Penosil Premium SilAcryl Exterior&Interior

---

- 2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):**  
Batch number: see packaging of the product

---

- 3. Intended use or uses of the construction product:**  
Sealant for facade for interior and exterior application, suitable for cold climates.  
Sealant used for sanitary applications.

---

- 4. Construction product in accordance with applicable harmonised specifications:**  
EN 15651-1:2012: Type F-INT-EXT-CC: CLASS 12,5E  
EN 15651-3:2012: Type S: CLASS XS2

---

- 5. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):**  
OÜ KRIMELTE  
Suur-Paala 10  
13619 Tallinn  
ESTONIA

---

- 6. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**  
Not relevant (see 5)

---

- 7. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:**  
System 3 for the type testing. / System 4 for the reaction to fire

---

- 8. In case of the declaration of performance concerning a construction product covered by a harmonised standard:**  
FUNDACION TECNALIA RESEARCH & INNOVATION (notified body nr. 1292) performed type testing under system 3 and issued test reports.

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

**DoP Nr: KR-043001**



Version 3 / November 2020

**9. Declared performance:**

<u>Essential characteristics:</u>	<u>Performance:</u>	<u>Harmonised technical specification</u>
<b>Reaction to fire</b>	Class F	EN 15651-1: 2012 EN 15651-3: 2012
<b>Release of chemicals dangerous to the environment and health</b>	NPD	
<b>Water tightness and air tightness, as:</b>		
• Resistance to flow (ISO 7390)	≤ 3 mm	
• Loss of volume (ISO 10563)	≤ 25 %	
• Adhesion/cohesion properties at maintained extension after water immersion. (EN ISO 10590)	NF	
• Tensile properties (i.e at maintained extension) at -30 °C. (EN ISO 8340)	NF	
• Adhesion/cohesion properties at variable temperatures (EN ISO 9047)	NF	
• Microbiological growth (ISO 846)	2	
<b>Durability:</b>	Pass	
Conditioning method B / Tested on mortar M2, without primer		

NPD = No performance determined.

NF= No Failure

**10. Declaration:**

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Kuldar Kongo  
Product Manager  
13619 Tallinn, Estonia  
30/11/2020