

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)



**DoP Nr: KR-019001**

Version 2 / September 2018

Page 1 of 2

---

**1. Unique identification code of the product-type:**

PENOSIL Premium PU-Sealant High Modulus

---

**2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):**

Batch number: see packaging of the product

---

**3. Intended use or uses of the construction product:**

Sealant for facade for interior and exterior application, intended for use in cold climate.

Sealant used for pedestrian walkways for interior and exterior application, intended for use in cold climate.

---

**4. Construction product in accordance with applicable harmonised specifications:**

EN 15651-1:2012: Type F-EXT-INT-CC: CLASS 25HM

EN 15651-4:2012: Type PW-EXT-INT-CC: CLASS 25HM

---

**5. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):**

OÜ KRIMELTE  
Suur-Paala 10  
13619 Tallinn  
ESTONIA

---

**6. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**

Not relevant (see 5)

---

**7. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:**

System 3 for the type testing.

---

**8. In case of the declaration of performance concerning a construction product covered by a harmonised standard:**

GINGER CEBTP (notified body nr. 0074) performed type testing and issued test reports.

---

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)



**DoP Nr: KR-019001**

Version 2 / September 2018

**9. Declared performance:**

<u>Essential characteristics:</u>	<u>Performance:</u>	<u>Harmonised technical specification</u>
<b>Reaction to fire</b>	Class E	EN 15651-1: 2012 EN 15651-4: 2012
<b>Release of chemicals dangerous to the environment and health</b>	NPD	
<b>Water tightness and air tightness, as:</b>		
• Resistance to flow	≤ 3 mm	
• Loss of volume	≤ 10 %	
• Adhesion/cohesion determination of tensile properties at maintained extension after immersion in water 23°C	NF	
• Adhesion/cohesion determination of tensile properties at maintained extension at -30°C	NF	
• Tear resistance	NF	
• Adhesion/cohesion determination of tensile properties at maintained extension after immersion in water (28 days)	NF	
• Adhesion/cohesion determination of tensile properties at maintained extension after immersion in salt water (28 days)	NF	
<b>Durability:</b>	Pass	
Conditioning method A/ Tested on mortar M1, without primer		

**10. Declaration:**

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Kuldar Kongo

Product Manager  
13619 Tallinn, Estonia  
07/09/2018