

Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)



DoP Nr: KR-044001

Version 1 / December 2016

Page 1 of 2

1. Unique identification code of the product-type:

PENOSIL Premium Aquabrake Fiber

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see packaging of the product

3. Intended use or uses of the construction product:

One component liquid-applied water impermeable product used beneath ceramic tiling.

4. Construction product in accordance with applicable harmonised specifications:

EN 14891:2012

5. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

OÜ KRIMELTE
Suur-Paala 10
13619 Tallinn
ESTONIA

6. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not relevant (see 5)

7. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 3 & 4 for the type testing.

8. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

VTT EXPERT SERVICES OY (notified body nr. 0809) performed the required parts of initial type testing according to harmonized standard EN 14891:2012 and its Annex ZA.

Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)



DoP Nr: KR-044001

Version 1 / December 2016

9. Declared performance:

<u>Essential characteristics:</u>	<u>Performance:</u>	<u>Harmonised technical specification</u>
Initial tensile adhesion strength	≥0,5 N/mm ²	EN 14891: 2012
Tensile adhesion strength after water contact	≥0,5 N/mm ²	
Tensile adhesion strength after heat ageing	≥0,5 N/mm ²	
Tensile adhesion strength after freeze-thaw cycles	≥0,5 N/mm ²	
Tensile adhesion strength after contact with lime water	≥0,5 N/mm ²	
Waterproofing	No penetration	
Crack bridging ability under standard conditions	≥0,75 mm	

10. Declaration:

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Kuldar Kongo

Product Manager
13619 Tallinn, Estonia
20/12/2016