

TECHNICAL DATASHEET

PENOSIL Premium Cleaning Wipes

Industrial cleaning wipes for the removal of construction chemistry and finishing agent residues from hands, tools and various surfaces. Quick and efficient.

FieldS of application

Suitable for the removal of paint, adhesive, PU foam, sealants, grease, oil, lubricants, ink, permanent marker, etc. from hands, tools and working surfaces.

Suitable for the removal of oil, lubricating grease and impurities from most surfaces, allows refreshing and cleaning old painted surfaces and sealing spots.

Application conditions

For better results, remove all stains immediately. The product might not remove fully dried stains. Before using the product, test its suitability in a hidden area. Not suitable for some plastics, delicate surfaces and textiles as it may remove or bleach the colour. Close the pot tightly every time after use.

Application instruction

Pull the cap off, remove the foil insulation, and pull the top end of the wipe from the middle of the roll by guiding it through the opening in the cover. Place the cover back to the pot and tear off the wipe from the perforated area. Leave the end of the next wipe in the plug and close tightly.

In order to soften paint stains, place the wipe for a few minutes on the stain and rub off the stain.

Technical specification

Property	Unit	Value
pH		5,5±0,2
VOC Content	%	<5 approx.

Package

Plastic pot - 50 wipes 15,6x21,3 cm in the pot, 6 pots in a package.

Storage

Storage time 24 months when stored in a closed package and dry places at temperatures +5 °C to +30 °C.

Safety requirements

Keep out of the reach of children. Keep out of heat sources and open flame. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice if symptoms persist.

Note: The instructions in the present documentation are based on tests carried out by the manufacturer and are presented in good faith. Due to variations in materials and substrates as well as the various application possibilities that are beyond our control, the manufacturer is not liable for the results achieved. In any case, it is recommended to test the product suitability at the place of application. Manufacturer reserves the right to modify products without prior notice.